



Grid Power 800-2HT M8V0 (2V800Ah)

Applications

- Uninterruptible power supply (UPS)
- Telecommunication base station
- High temperature station without air-condition
- Station in the open air

Certificates



Conform to
IEC60896-21&22







Specifications

Nominal Voltage	2V	Operating Temp. Range	Discharge:	-40~65°C
Nominal Capacity	800Ah (C ₁₀ 1.80V/cell)		Charge:	-20~45°C
Approx. Weight	50.4kg		Storage:	-20~50°C
Terminal	M8	Standby Use	Initial Charging Current less than 200A. Voltage 2.25V at 35°C. Temperature Coefficient -3mV/°C.	
Container Material	ABS UL94 V0	Capacity affected by Temp.	40°C	103%
Rated Capacity (35°C)	848.0Ah/42.4A, 20hr, 1.80V/cell 800.0Ah/80.0A, 10hr, 1.80V/cell 710.5Ah/142.1A, 5hr, 1.75V/cell 626.0Ah/212.0A, 3hr, 1.75V/cell 512.9Ah/512.9A, 1hr, 1.60V/cell		35°C	100%
Max. Discharge Current	6400A (5s)	Self Discharge	0°C	86%
Internal Resistance / Impedance (1kHz)	Approx. 0.4mΩ		SSB Grid Power batteries may be stored for up to 6 months at 25°C/3 months at 35°C and then a freshening charge is required. For higher temperatures the time interval will be shorter.	
Nominal Oper. Temp. R.	35 (+5/-15)°C	Life Expectancy	Classified as „Very Long Life“ according EUROBAT.	

Dimensions

■ M8 Terminal

Unit: mm | Dimensions: 410 Length X 175 Width X 330 Height (350 Height incl. Terminal)




Constant Current Discharge (Amperes) at 35°C

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	933.4	792.0	722.9	650.4	547.2	448.0	376.8	249.6	192.5	155.4	131.0	114.3	91.2	76.5	40.5
1.80V/cell	1136.0	926.4	823.8	732.0	603.2	486.4	408.5	266.4	202.1	162.0	136.5	118.4	95.0	80.0	42.4
1.75V/cell	1327.7	1065.6	932.0	820.8	660.8	530.1	446.1	281.6	212.0	170.0	142.1	122.8	97.6	81.6	43.2
1.70V/cell	1519.5	1195.2	1030.1	892.8	710.4	562.1	472.0	295.6	221.3	176.0	146.3	126.7	100.5	83.6	44.3
1.67V/cell	1631.3	1286.4	1110.4	960.0	752.0	586.7	492.0	307.2	228.4	181.0	150.3	129.6	101.8	85.0	45.0
1.60V/cell	1776.0	1377.6	1177.6	1008.0	785.6	612.3	512.9	318.8	233.8	185.0	153.5	132.0	103.6	85.8	45.4


Constant Power Discharge (Watts/cell) at 35°C

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	1743.2	1490.0	1368.7	1237.1	1045.8	861.4	728.8	485.5	376.2	304.8	258.1	225.8	181.0	152.1	80.6
1.80V/cell	2086.9	1717.5	1539.6	1377.6	1143.5	929.0	785.7	515.7	393.1	316.7	267.7	233.0	188.0	158.9	84.3
1.75V/cell	2396.6	1944.2	1717.2	1527.1	1243.2	1006.6	854.2	543.0	411.3	331.2	277.7	240.9	192.7	161.9	85.9
1.70V/cell	2697.0	2150.2	1878.6	1646.9	1325.3	1060.0	899.0	567.6	427.8	341.4	285.1	248.1	198.2	165.7	87.9
1.67V/cell	2843.3	2279.8	1999.8	1751.8	1392.4	1100.0	931.9	587.3	439.5	350.0	291.9	253.1	200.2	168.1	89.2
1.60V/cell	3031.6	2393.6	2085.8	1818.4	1440.0	1137.3	964.7	605.7	447.5	356.1	296.8	257.0	203.4	169.4	89.8


Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Cycle Service Life in Relation to Depth of Discharge

